



Meanwell non-waterproof power supplies

Constant voltage 12V - 24V - 48V

Power supplies with a constant voltage Meanwell (not waterproof). **We offer a 2 year guarantee.**

Reference	Tension	Power	Amps	Power factor	Waterproofing	Weight	Measurements (mm)
39.010	12V	150W	12.5A	>0.5	IP20	500g	160x98x30
39.011	12V	320W	25A	>0.5	IP20	900g	215x115x30
39.017	24V	150W	6.5A	>0.5	IP20	500g	160x98x30
39.018	24V	320W	13,3A	>0.5	IP20	900g	215x115x30
39.002	48V	500W	10,5A	>0.9	IP20	900g	230x127x40.5



Meanwell waterproof power supplies

Constant voltage 5V - 12 V - 24V

Power supplies with a constant voltage Meanwell (waterproof). **We offer a 2 year guarantee.**

Reference	Tension	Power	Amps	Power factor	Waterproofing	Weight	Measurements (mm)
39.003	5V	25W	5A	>0.5	IP67	340g	148x40x30
39.004	5V	40W	8A	>0.5	IP67	400g	160x40x30
39.005	12V	18W	1.5A	>0.5	IP67	220g	140x30x24
39.006	12V	36W	3A	>0.5	IP67	340g	148x40x30
39.007	12V	60W	5A	>0.5	IP67	400g	163x43x32
39.008	12V	100W	8.5A	>0.5	IP67	630g	190x52x37
39.009	12V	120W	10A	>0.5	IP67	500g	191x63x37.5
39.019	12V	480W	40A	>0.9	IP67	900g	280x144x48.5
39.012	24V	18W	0.75A	>0.5	IP67	220g	118x35x26
39.013	24V	36W	1.5A	>0.5	IP67	340g	140x30x24
39.014	24V	60W	2.5A	>0.5	IP67	400g	163x43x32
39.015	24V	100W	4.2A	>0.5	IP67	630g	190x52x39
39.016	24V	150W	6.3A	>0.5	IP67	700g	228x68x39

ecoled non-waterproof power supplies

Constant voltage 12V - 24V



Ultra-thin



Compact



We offer our own brand name “ecoled” power supplies which are compact and ultra-thin with a constant output voltage. **We offer a 5 year guarantee.**
In compliance with lighting apparatus standards: EN-61347-1-2-13. EN-61547. EN-61000-3-2. EN-62384. EN-55015.

Reference	Tension	Power	Amps	Power factor	Waterproofing	Weight	Measurements (mm)
40.006	12V	20W	1.66A	>0.9	IP20	62g	123x42x20
40.001	Ultra-thin 12V	30W	2.5A	>0.95	IP20	105g	245x30x14
40.004	Compact 12V	36W	3A	>0.5	IP20	180g	84x28x42
40.007	12V	60W	5A	>0.9	IP20	310g	180x50x32
40.008	12V	100W	8.33A	>0.9	IP20	350g	300x38x30
40.009	24V	30W	1.25A	>0.9	IP20	62g	153x42x32
40.002	Ultra-thin 24V	30W	1.25A	>0.95	IP20	146g	245x30x14
40.005	Compact 24V	36W	1.5A	>0.5	IP20	180g	84x28x42
40.003	Ultra-thin 24V	60W	2.5A	>0.98	IP20	170g	290x45x18
40.010	24V	75W	3.12A	>0.9	IP20	310g	180x50x32
40.011	24V	120W	5A	>0.9	IP20	350g	300x38x30
40.012	24V	180W	7.5A	>0.9	IP20	450g	350x50x30

ecoled waterproof power supplies

Constant voltage 24V



IP67 waterproof power supplies with a constant current output ecoled. **We offer a 5 year guarantee.**

In compliance with lighting apparatus standards: EN-61347-1-2-13. EN-61547. EN-61000-3-2. EN-62384. EN-55015.

Reference	Tension	Power	Amps	Power factor	Waterproofing	Weight	Measurements (mm)
40.015	24V	200W	8.33A	>0.8	IP67	920g	230x90x43
40.016	24V	320W	13.33A	>0.9	IP67	1300g	236x97x40

Vossloh non-waterproof power supplies

Constant voltage 12V - 24V - 48V

Power supplies with a constant voltage, Vossloh (German brand) specially indicated for lighting.
We offer a 5 year guarantee. In compliance with lighting apparatus standards: EN-61347-2-13.



Reference	Tension	Power	Amps	Power factor	Waterproofing	Weight	Measurements (mm)
38.002	12V	20W	1.68A	>0.5	IP20	100g	123x45x19
38.003	12V	60W	5A	>0.9	IP20	310g	180x52x30
38.004	12V	75W	6.25A	>0.9	IP20	380g	180x52x30
38.005	12V	100W	8.40A	>0.9	IP20	440g	300x40x30
38.006	24V	30W	1.25A	>0.9	IP20	140g	153x41x32
38.021 (DALI2/1-10V)	24V	30W	1.25A	>0.95	IP20	550g	359x30x21
38.007	24V	60W	2.5A	>0.9	IP20	310g	180x52x30
38.008	24V	75W	3.12A	>0.9	IP20	380g	180x52x30
38.022 (DALI2/1-10V)	24V	70W	2.91A	>0.95	IP20	550g	359x30x21
38.009	24V	120W	5A	>0.9	IP20	440g	300x40x30
38.023 (DALI2/1-10V)	24V	120W	5A	>0.95	IP20	550g	359x30x21
38.010	24V	180W	7.5A	>0.9	IP20	665g	345x50x35
38.001	48V	120W	2.5A	>0.95	IP20	410g	300x30x40

Vossloh non-waterproof power supplies

Constant current 350mA - 500mA - 700mA

Power supplies with a constant current, Vossloh (German brand) specially indicated for lighting.
We offer a 5 year guarantee. In compliance with lighting apparatus standards: EN-61347-2-13.

Reference	Control	Power	350mA	500mA	700mA	Size
38.013	No	6-14W	✓	✗	✗	230x30x21
38.014	No	12-21W	✗	✓	✓	230x30x21
38.017	1-10V	12-80W	✗	✓	✓	425x30x21
* Power supplies with 2 channels each of 40W						
38.012	No	20-40W	✓	✓	✓	360x30x21
38.015	DALI/PUSH	21-42W	✓	✓	✓	358x30x21
38.011	No	42-80W	✓	✓	✓	360x30x21
38.016	DALI/PUSH	42-84W	✓	✓	✓	358x30x21
38.019	No	70-120W	✗	✓	✓	280x30x21
38.020	No	95-165W	✗	✓	✓	359x30x21

