

VENUS 60



On/Off

**Ref: 80.071** skyled Venus 60 lacado blanco - 6500K / skyled Venus 60 white lacquered - 6500K

**Ref: 80.072** skyled Venus 60 lacado blanco - 4000K / skyled Venus 60 white lacquered - 4000K

**Ref: 80.073** skyled Venus 60 lacado blanco - 2700K / skyled Venus 60 white lacquered - 2700K

**Ref: 80.070** skyled Venus 60 lacado blanco - 1900K-6500K / skyled Venus 60 white lacquered - 1900K- 6500K

**Ref: 80.083** skyled Venus 60 lacado negro - 6500K / skyled Venus 60 black lacquered - 6500K

**Ref: 80.084** skyled Venus 60 lacado negro - 4000K / skyled Venus 60 black lacquered - 4000K

**Ref: 80.085** skyled Venus 60 lacado negro - 2700K / skyled Venus 60 black lacquered - 2700K

**Ref: 80.082** skyled Venus 60 lacado negro - 1900K-6500K / skyled Venus 60 black lacquered - 1900K- 6500K

Colgante / Hanging

max. 4000

Escala 1:1 / Scale 1:1 (mm)

25

40

Escala 1:25 / Scale 1:25 (mm)

Ø600

Ø550

Curvas fotométricas / Photometric curves

12  
24  
36  
48  
60

— C0/180  
— C90/270

Características técnica / Technical data

|                                              |                                                                                            |                                           |                           |
|----------------------------------------------|--------------------------------------------------------------------------------------------|-------------------------------------------|---------------------------|
| Potencia luminaria / Luminaire power         | 40.5W                                                                                      | Control / Control                         | On-Off                    |
| Flujo luminaria / Luminaire flux             | 1716 lm (6500K)<br>1691 lm (4000K)<br>1598 lm (2700K)<br>1125 lm - 1716 lm (1900K - 6500K) | Alimentación eléctrica / Electric feed    | 220~240V, 50/60Hz         |
| Eficiencia lumínica / Luminous efficiency    | 42 lm/W                                                                                    | Sistema óptico / Optical system           | difusor opal / opal cover |
| Eficiencia energética / Energetic efficiency |                                                                                            | Material perfil / Profile material        | AL6063-T5                 |
| CCT                                          | 6500K / 4000K / 2700K / 1900K-6500K                                                        | Dimensiones / Measurements                | Ø600 x 25 x 40 mm         |
| IRC / CRI                                    | >80                                                                                        | Temperatura trabajo / Working temperature | -20°C ~ 40°C              |
| Ángulo de apertura / Opening angle           | 105°                                                                                       | Vida útil / Lifespan                      | 50.000 h                  |

