

NEPTUNO 50



On/Off

Ref: 80.095 skyled Neptuno 50 lacado blanco - 6500K / *skyled Neptuno 50 white lacquered - 6500K*

Ref: 80.096 skyled Neptuno 50 lacado blanco - 4000K / *skyled Neptuno 50 white lacquered - 4000K*

Ref: 80.097 skyled Neptuno 50 lacado blanco - 2700K / *skyled Neptuno 50 white lacquered - 2700K*

Ref: 80.094 skyled Neptuno 50 lacado blanco - 1900K-6500K / *skyled Neptuno 50 white lacquered - 1900K- 6500K*

Ref: 80.107 skyled Neptuno 50 lacado negro - 6500K / *skyled Neptuno 50 black lacquered - 6500K*

Ref: 80.108 skyled Neptuno 50 lacado negro - 4000K / *skyled Neptuno 50 black lacquered - 4000K*

Ref: 80.109 skyled Neptuno 50 lacado negro - 2700K / *skyled Neptuno 50 black lacquered - 2700K*

Ref: 80.106 skyled Neptuno 50 lacado negro - 1900K-6500K / *skyled Neptuno 50 black lacquered - 1900K- 6500K*

Colgante / *Hanging*

max. 4000

Escala 1:1 / *Scale 1:1 (mm)*

Escala 1:25 / *Scale 1:25 (mm)*

Curvas fotométricas / *Photometric curves*

Características técnica / *Technical data*

Potencia luminaria / <i>Luminaire power</i>	36.2W	Control / <i>Control</i>	On-Off
Flujo luminaria / <i>Luminaire flux</i>	1202 lm (6500K) 1183 lm (4000K) 1119 lm (2700K) 788 lm - 1202 lm (1900K - 6500K)	Alimentación eléctrica / <i>Electric feed</i>	220~240V, 50/60Hz
Eficiencia lumínica / <i>Luminous efficiency</i>	33 lm/W	Sistema óptico / <i>Optical system</i>	difusor opal / <i>opal cover</i>
Eficiencia energética / <i>Energetic efficiency</i>		4,859 mm	AL6063-T5
CCT	6500K / 4000K / 2700K / 1900K-6500K	Dimensiones / <i>Measurements</i>	Ø500 x 25 x 40 mm
IRC / CRI	>80	Temperatura trabajo / <i>Working temperature</i>	-20°C ~ 40°C
Ángulo de apertura / <i>Opening angle</i>	105°	Vida útil / <i>Lifespan</i>	50.000 h

