





Referencia / Code		Largo / Length	Potencia / Power	Tª Color / Colour T.	Ángulo / Angle	Acabado / Finish	RAL
ON/OFF	DALI						
82.249	82.349	173 cm	28W	3000K	30°	Blanco / White	
82.250	82.350	173 cm	28W	4000K	30°	Blanco / White	
82.251	82.351	173 cm	28W	3000K	65°	Blanco / White	
82.252	82.352	173 cm	28W	4000K	65°	Blanco / White	
82.253	82.353	173 cm	28W	3000K	30°	Negro / Black	
82.254	82.354	173 cm	28W	4000K	30°	Negro / Black	
82.255	82.355	173 cm	28W	3000K	65°	Negro / Black	
82.256	82.356	173 cm	28W	4000K	65°	Negro / Black	



Referencia / Code		Largo / Length	Potencia / Power	Tª Color / Colour T.	Ángulo / Angle	Acabado / Finish	RAL
ON/OFF	DALI						
82.257	82.357	173 cm	42W	3000K	30°	Blanco / White	
82.258	82.358	173 cm	42W	4000K	30°	Blanco / White	
82.259	82.359	173 cm	42W	3000K	65°	Blanco / White	
82.260	82.360	173 cm	42W	4000K	65°	Blanco / White	
82.261	82.361	173 cm	42W	3000K	30°	Negro / Black	
82.262	82.362	173 cm	42W	4000K	30°	Negro / Black	
82.263	82.363	173 cm	42W	3000K	65°	Negro / Black	
82.264	82.364	173 cm	42W	4000K	65°	Negro / Black	


CARACTERÍSTICAS TÉCNICAS / TECHNICAL DATA

Potencia luminaria / Luminaire power	34.8 W / 52.2 W
Flujo luminaria / Luminaire luminous flux	3072 lm / 4609 lm (3000 K, 65°) 3239 lm / 4858 lm (4000 K, 65°)
Eficiencia lumínica / Luminous efficiency	93 lm / W
Eficiencia energética / Energetic efficiency	
CCT	3000 K / 4000 K
CRI	> 90
UGR (4H/8H)	< 16
Dimensiones / Dimensions	173 x 3.5 x 2.5 cm

Potencia fuente de luz / Light source power	28 W / 42 W
Flujo fuente de luz / Light source luminous flux	4200 lm / 6300 lm (3000 K) 4380 lm / 6570 lm (4000 K)
Control / Control	ON/OFF - DALI
Corriente / Current	350 mA
Alimentación eléctrica / Electrical feed	220...240V, 50/60Hz
Temperatura trabajo / Operating temperature	-20°C ~ 30°C
Vida útil / Lifespan	50.000 h (L80/B10)




DATOS FOTOMÉTRICOS / PHOTOMETRIC DATA



Reflector negro / Black reflector
30°
4000K

TABLA UGR / UGR TABLE

glare rating regarding UGR											
p ceiling		70	70	50	50	30	70	70	50	50	30
p walls		50	30	50	30	30	50	30	50	30	30
p floor		20	20	20	20	20	20	20	20	20	20
room size X Y		viewed crosswise					viewed endwise				
2H	2H	12.5	13.2	12.7	13.4	13.6	14.3	15.0	14.6	15.2	15.4
2H	3H	12.4	13.0	12.6	13.2	13.5	14.2	14.8	14.5	15.0	15.3
2H	4H	12.3	12.9	12.6	13.1	13.4	14.1	14.7	14.4	14.9	15.2
2H	6H	12.2	12.8	12.5	13.0	13.3	14.0	14.6	14.4	14.8	15.1
2H	8H	12.2	12.7	12.5	13.0	13.3	14.0	14.5	14.3	14.8	15.1
2H	12H	12.1	12.6	12.5	12.9	13.2	14.0	14.4	14.3	14.7	15.1
4H	2H	12.3	12.9	12.6	13.1	13.4	14.1	14.7	14.4	14.9	15.2
4H	3H	12.2	12.6	12.5	12.9	13.3	14.0	14.4	14.3	14.7	15.1
4H	4H	12.1	12.5	12.5	12.8	13.2	13.9	14.3	14.3	14.6	15.0
4H	6H	12.0	12.4	12.4	12.7	13.1	13.8	14.2	14.2	14.5	14.9
4H	8H	12.0	12.3	12.4	12.7	13.1	13.8	14.1	14.2	14.5	14.9
4H	12H	11.9	12.2	12.4	12.6	13.0	13.7	14.0	14.2	14.4	14.8
8H	4H	12.0	12.3	12.4	12.7	13.1	13.8	14.1	14.2	14.5	14.9
8H	6H	11.9	12.1	12.3	12.5	13.0	13.7	13.9	14.1	14.3	14.8
8H	8H	11.8	12.0	12.3	12.5	12.9	13.6	13.8	14.1	14.3	14.7
8H	12H	11.8	11.9	12.3	12.4	12.9	13.6	13.7	14.1	14.2	14.7
12H	4H	11.9	12.2	12.4	12.6	13.0	13.7	14.0	14.2	14.4	14.8
12H	6H	11.8	12.0	12.3	12.5	12.9	13.6	13.8	14.1	14.3	14.7
12H	8H	11.8	11.9	12.3	12.4	12.9	13.6	13.7	14.1	14.2	14.7
variation of observer position for luminaire distances S											
S = 1.0H S = 1.5H S = 2.0H		+4.3 / -14.9 +6.9 / -20.8 +8.9 / -25.6					+4.1 / -13.3 +6.8 / -21.0 +8.8 / -26.9				
standard table		BK00					BK00				
correction summand		-6.4					-4.6				
corrected glare indices based on the total luminous flux UGR diagram according to CIE 117 with SHR 0.25											



Reflector negro / Black reflector
65°
4000K

TABLA UGR / UGR TABLE

glare rating regarding UGR											
p ceiling		70	70	50	50	30	70	70	50	50	30
p walls		50	30	50	30	30	50	30	50	30	30
p floor		20	20	20	20	20	20	20	20	20	20
room size X Y		viewed crosswise					viewed endwise				
2H	2H	15.4	16.1	15.7	16.2	16.4	16.2	16.8	16.4	17.0	17.2
2H	3H	15.3	15.9	15.6	16.1	16.3	16.0	16.6	16.3	16.8	17.1
2H	4H	15.2	15.8	15.5	16.0	16.3	16.0	16.5	16.3	16.8	17.0
2H	6H	15.1	15.6	15.5	15.9	16.2	15.9	16.4	16.2	16.7	16.9
2H	8H	15.1	15.6	15.4	15.9	16.2	15.8	16.3	16.2	16.6	16.9
2H	12H	15.1	15.5	15.4	15.8	16.1	15.8	16.3	16.2	16.6	16.9
4H	2H	15.2	15.8	15.5	16.0	16.3	16.0	16.5	16.3	16.8	17.0
4H	3H	15.1	15.5	15.4	15.8	16.1	15.8	16.3	16.2	16.6	16.9
4H	4H	15.0	15.4	15.4	15.7	16.1	15.7	16.1	16.1	16.5	16.8
4H	6H	14.9	15.2	15.3	15.6	16.0	15.7	16.0	16.1	16.3	16.7
4H	8H	14.9	15.2	15.3	15.5	15.9	15.6	15.9	16.0	16.3	16.7
4H	12H	14.8	15.1	15.3	15.5	15.9	15.6	15.8	16.0	16.2	16.6
8H	4H	14.9	15.2	15.3	15.5	15.9	15.6	15.9	16.0	16.3	16.7
8H	6H	14.8	15.0	15.2	15.4	15.9	15.5	15.7	16.0	16.2	16.6
8H	8H	14.7	14.9	15.2	15.4	15.8	15.5	15.7	16.0	16.1	16.6
8H	12H	14.7	14.8	15.2	15.3	15.8	15.4	15.6	15.9	16.0	16.5
12H	4H	14.8	15.1	15.3	15.5	15.9	15.6	15.8	16.0	16.2	16.6
12H	6H	14.7	14.9	15.2	15.4	15.8	15.5	15.7	16.0	16.1	16.6
12H	8H	14.7	14.8	15.2	15.3	15.8	15.4	15.6	15.9	16.0	16.5
variation of observer position for luminaire distances S											
S = 1.0H S = 1.5H S = 2.0H		+5.4 / -21.6 +8.2 / -29.6 +10.2 / -33.5					+5.4 / -23.5 +8.2 / -32.6 +10.2 / -35.5				
standard table		BK00					BK00				
correction summand		-3.3					-2.6				
corrected glare indices based on the total luminous flux UGR diagram according to CIE 117 with SHR 0.25											