

DIGITAL LED

FIJI

TIRAS FLEXIBLES

Ref: 35.001

RGB DIGITAL

Tira flexible con led digital RGB serie "PRO"

IP20 con 60 leds/metro y cortable cada led.


Requiere uso de led profile para disipación.

PCB de 5 mm.

Conexión máxima en circuito abierto: 2m.


Vida útil: 50.000h*

*En función de la disipación del perfil, de las horas diarias trabajadas y de la temperatura externa ambiental de trabajo.



Potencia (W)	11.5W/m
Voltaje (V)	5V
Tipo de IC	SK6812
Lumens	308 Lm/m
CRI	>50
Control del led	led a led
Emisión de luz	120°
Estanqueidad (IP)	IP20
Nº leds/m	60
Medidas	5000x5x2.5mm
Cortable	cada 16.54mm
PCB	5mm
Temperatura trabajo	-20°C / +60°C
Apto para	interior
Embalaje	1 rollo/5m
Garantía	3 años

Aprobado por: CE RoHS COMPLIANT




BARCELONA
C/ Carles Buhigues, 13
08420 Canovelles
Info@luznegra.net
Tel: +34 938 402 598

MADRID
C/ Minas, 35-37
28923 Alcorcón
centro@luznegra.net
Tel: +34 916 416 081

PARIS
113 Avenue Joffre
77450 Esbly
france@luznegra.net
Tel: +33 (0) 160 426 585

Spectrum Test Report



Color Parameters:

Chromaticity Coordinate: $x=0.2550$ $y=0.2657$ $u'=0.1796$ $v'=0.4211$
 CCT=17787K (Duv=0.0052) Dominant WL:Ld =479.4nm Purity=32.7%
 Ratio:R=21.2% G=67.3% B=11.5%; Peak WL:Lp=464.2nm FWHM=19.2nm
 Render Index:Ra=51.0 CRI=47.1 TM30:Rf=48 Rg=114
 R1 =34 R2 =64 R3 =77 R4 =54 R5 =56 R6 =65 R7 =57
 R8 =0 R9 =0 R10=24 R11=47 R12=61 R13=38 R14=82 R15=10

Photo Parameters:

Flux = 308.1 lm Eff. : 27.68 lm/W Fe = 1.340 W Scotopic:1151.2 S/P:3.7366





Electrical parameters:

V = 4.9998 V I = 2.226 A P = 11.13 W PF = 1.000

Status: Integral T = 1328 ms Ip = 53709 (82%)


Model:Ecoled Fiji	Number: 35.001
Tester:Sergio Carneros	Date:26-5-2021
Temperature:25Deg	Humidity:57%
Manufacturer:Luz Negra S.L	Remarks:100cm de tira flexible

Rf: 48 CCT: 17787 K u': 0.1796
Rg: 114 Duv: 0.0052 v': 0.4211



Model:Ecoled Fiji
Tester:Sergio Carneros
Temperature:25Deg
Manufacturer:Luz Negra S.L

Number: 35.001
Date:26-5-2021
Humidity:57%
Remarks:100cm de tira flexible



Hue Bin	Hue Angle	Rf	Graphic shift(%)	
			Chroma	Hue
1	0.0° - 22.5°	18	40	4
2	22.5° - 45.0°	8	29	-23
3	45.0° - 67.5°	30	21	-45
4	67.5° - 90.0°	18	-2	-37
5	90.0° - 112.5°	50	-21	-16
6	112.5° - 135.0°	75	-2	9
7	135.0° - 157.5°	63	7	15
8	157.5° - 180.0°	55	17	14
9	180.0° - 202.5°	68	22	8
10	202.5° - 225.0°	63	14	-8
11	225.0° - 247.5°	65	14	-13
12	247.5° - 270.0°	56	-1	-18
13	270.0° - 292.5°	75	-6	0
14	292.5° - 315.0°	39	0	31
15	315.0° - 337.5°	36	15	34
16	337.5° - 360.0°	36	23	18

Model:Ecoled Fiji
 Tester:Sergio Carneros
 Temperature:25Deg
 Manufacturer:Luz Negra S.L

Number: 35.001
 Date:26-5-2021
 Humidity:57%
 Remarks:100cm de tira flexible