

# led profile by Luz Negra

Our PROFESSIONAL led profile series for surfaces/hanging applications is manufactured in high purity aluminium and lacquered in textured white, black and grey. Drivers can be housed inside.

The internal tray allows us to screw the 20mm rigid led strip on one side and enables us to house the power supply on the other. At the same time this tray can be removed from the front which means easy maintenance. For safety measures, we recommend the fixing of a braided cable from the profile base to the dissipation tray. Both profile and cover are available in 3.4 metre lengths.

**We offer a 5 year guarantee on the profiles and covers.**

## GALES ASYMMETRIC



### Aluminium profile

16.012	lacquered white	3.40m
16.013	lacquered black	3.40m
16.011	lacquered grey	3.40m



### Aluminium tray

14.022	textured white	3.40m
14.023	textured black	3.40m
14.024	textured grey	3.40m



### Polycarbonate cover

18.079	frosted	3.40m
--------	---------	-------



### Aluminium endcaps

19.246	grey
19.247	white
19.248	black



### Profile joints

22.219	steel
--------	-------




### Hanging kit

21.001	chrome	set of 2 units
21.002	white	set of 2 units
21.003	black	set of 2 units



### Safety cable

22.039	steel	18cm
--------	-------	------



System with front removable tray which permits easy access to the led strip and power supply, therefore allowing very fast and simple maintenance of the electrical installation.



Aluminium alloy extrusion process in accordance with: ISO 9001:2008 - ISO 14001 / Tolerances defined by: UNE-EN 755-9 / UNE-EN 12020-2  
Theoretical weight: 1.202Kg / Alloy: 6060 / Perimeter: 552mm / Anodising minimum: 15 microns  
Purity aluminium: 95-98% / Treatment: T-5