

Our PROFESSIONAL led profile for surfaces (only 4.05mm high) is manufactured in high purity anodised aluminium and available in two different colours (the profile can also be supplied in raw aluminium with no coating of paint).

The profile is ideal for using on wall surfaces, furniture, shelves and similar areas, where we require a minimalist profile with very reduced dimensions.

Its cover (available in 5 different finishes), has our "easy-ON" system. Once combined with this profile, it provides an IP65 rating to the luminaire.

This can be used in places with high levels of humidity, for example bathrooms, kitchens, gyms, spas, cold storage chambers, fridges, and others.

The profile and its covers are available in lengths of 2 and 6 metres, thus allowing us to carry out large projects where all profiles do not have joints or similar surface breaks.

It is suitable for led strips with a maximum length of 10mm, whose power level does not exceed 15W/m. In order to obtain a more homogeneous and diffused illumination, we recommend using with our opal cover with COB ecoled strips.

**We offer a 10 year guarantee on the profiles and a 4 year guarantee on the covers.**

## MILANO SLIM



IP65



Scale 1:1



Scale 1:2




### Aluminium profile

01.016	anodised silver	2m
01.017	anodised black	2m
01.018	anodised silver	6m
01.019	anodised black	6m



### Plastic endcaps

19.206	grey without hole
19.207	grey with hole
19.208	black without hole
19.209	black with hole



### Clip

20.066	plastic
--------	---------



### Hanging KIT


21.001	chrome	set of 2 units
21.002	white	set of 2 units
21.003	black	set of 2 units

(clip not included)



### Polycarbonate cover "easy-ON"

18.001	transparent	2m
18.002	opal	2m
18.003	frosted	2m
18.004	transparent	6m
18.005	opal	6m
18.006	frosted	6m
18.134	frosted	60m



### Black&White cover "easy-ON"

18.007	Black&White	2m
18.008	opaque grey	2m
18.009	Black&White	6m

### Polycarbonate cover "easy-ON"

18.136	microprism	2m
18.135	microprism	6m




### Methacrylate UV cover "easy-ON"

18.179	frosted	2m
18.178	frosted	6m



### Profile bending machine

22.031	22cm Ø minimum profile curvature
--------	----------------------------------



Aluminium alloy extrusion process in accordance with: ISO 9001:2008 - ISO 14001 / Tolerances defined by: UNE-EN 755-9 / UNE-EN 12020-2  
Theoretical weight: 0.089kg / Alloy: 6063 / Perimeter: 52mm / Anodising minimum: 15 microns  
Aluminium purity: 95-98% / Material treatment: T-5 / Covers: methacrylate (greater protection against UV rays)