



Our BASIC led profile series for surfaces is manufactured in high purity aluminium and available in anodised silver, lacquered white, lacquered black and raw aluminium (on demand we can supply different anodised and lacquered finishes). Ideal for wall surfaces, furniture, shelves and similar. Suitable for led strips with a maximum width of 14mm and a power not greater than 30W/m. In order to obtain a more homogeneous illumination, while also making the dots invisible, we recommend the combined use of both our frosted cover and Canovelles-Barcelona-Gomera-COB ecoled strips.

We offer a 2 year guarantee on our profiles and covers.



Scale 1:2

Scale 1:1



Aluminium profile

02.012	anodised silver	2m
02.013	white lacquered	2m
02.014	raw	2m
02.038	black lacquered	2m
02.015	anodised silver	6m
02.016	white lacquered	6m
02.017	raw	6m
02.037	black lacquered	6m

Plastic endcaps

19.030	white with hole
19.031	white without hole
19.032	grey with hole
19.033	grey without hole
19.441	black with hole
19.442	black without hole

Clip

20.005	transparent plastic
--------	---------------------




Embedding clip

20.003	chrome steel
	(clip not included)

90° angle bracket

22.001	steel (52x13mm)
--------	-----------------



Adhesive magnet

42.001	12mm	1m
--------	------	----



Polycarbonate cover

18.146	frosted	2m
18.148	opal	2m
18.152	transparent	2m
18.145	frosted	6m
18.147	opal	6m
18.151	transparent	6m



Methacrylate cover

18.014	transparent	2m
18.015	frosted	2m
18.016	transparent	6m
18.017	frosted	6m



Adjustable bracket

20.004	chrome steel
	(clip not included)



Aluminium alloy extrusion process in accordance with: ISO 9001:2008 - ISO 14001 / Tolerances defined by: UNE-EN 755-9 / UNE-EN 12020-2
Theoretical weight: 0.157kg / Alloy: 6063 / Perimeter: 92mm / Anodising minimum: 15 microns
Aluminium purity: 95-98% / Material treatment: T-5 / Covers: methacrylate (greater protection against UV rays)