led profile by Luz Negra

Our BASIC led profile series for angles and ceiling suspension is manufactured in high purity aluminium and available in anodised silver, lacquered white and raw aluminium (on demand, we can supply different anodised and lacquered finishings. This profile has a wide range of applications, examples of which include ceiling suspended luminaires, luminaires for displaying paintings, wardrobe garment rails, floor or wall mounted luminaires, and others.

It can be used with led strips with a maximum width of 12.5mm and a power not greater than 30W/m. In order to obtain a more homogeneous illumination, while also making the dots invisible, we recommend the combined use of both our frosted covers and Canovelles-Barcelona-Gomera-COB ecoled strips.


We offer a 2 year guarantee on our profiles and covers.

MIAMI



Scale 1:1







Aluminium profile

13.007	anodised silver	2m
13.008	white lacquered	2m
13.009	raw	2m
13.010	anodised silver	6m
13.011	white lacquered	6m
13.012	raw	6m



Plastic endcaps

19.091	white with hole
19.092	white without hole
19.093	grey with hole
19.094	grey without hole



clip

20.019 metal



MIAMI profile

+ hanging KIT "21.001"

Paris complements can also be used



Polycar	bonate cover	
18.146	frosted	2m
18.148	opal	2m
18.152	transparent	2m
18.145	frosted	6m
18.147	opal	6m
18.151	transparent	6m



Methacrylate cover

moundor y late de ver				
18.014	transparent	2m		
18.015	frosted	2m		
18.016	transparent	6m		
18.017	frosted	6m		



Supporting arm

22.006 silver anodised 22.007 black anodised Measurements: 170x50mm

* (clip not included)



Aluminium alloy extrusion process in accordance with: ISO 9001:2008 - ISO 14001 / Tolerances defined by: UNE-EN 755-9 / UNE-EN 12020-2 Theoretical weight: 0.265kg / Alloy: 6063 / Perimeter: 125mm / Anodising minimum: 15 microns Aluminium purity: 95-98% / Material treatment: T-5 / Covers: methacrylate (greater protection against UV rays)