

circular led profiles




PARIS

94



MIAMI

98



PARIS XL

100



OSLO
B&W

102

OSLO

103

Our PROFESSIONAL led profile series for surfaces and ceiling suspension is manufactured in high purity anodised aluminium and available in 3 different colours. The profile has a wide range of applications, examples of which include ceiling suspended luminaires, luminaires for displaying paintings, wardrobe garment rails, floor or wall mounted luminaires, and others.



Its "easy-ON" cover (available in 8 different finishings), when combined with this profile, provides an IP65 rating to the luminaire. Therefore, the profile can be used in places with high levels of humidity, for example bathrooms, kitchens, gyms, spas, cold storage chambers, fridges and others.

This profile and its covers are available in lengths of 2 and 6 metres, allowing us to carry out large projects where all the profiles do not need joints. It is suitable for led strips with a maximum width of 12mm and a power not greater than 30W/m. In order to obtain a more homogeneous and diffused illumination, we recommend the combined use of both our opal diffusers and Canovelles-Barcelona-Gomera-COB ecoled strips.

We offer a 10 year guarantee on the profiles and a 4 year guarantee on the covers.

Scale 1:1

When applying the lens cover on the Paris profile together with the flexible led strip we get a beam of 35° light.



Aluminium profile

13.001	anodised silver	2m
13.002	anodised black	2m
13.004	anodised silver	6m
13.005	anodised black	6m



Plastic endcaps

19.083	grey without hole
19.084	grey with hole
19.085	black without hole
19.086	black with hole



Plastic endcaps

19.087	grey without hole lens
19.088	grey with hole lens
19.089	black without hole lens
19.090	black with hole lens



Polycarbonate cover "easy-ON"

18.001	transparent	2m
18.002	opal	2m
18.003	frosted	2m
18.004	transparent	6m
18.005	opal	6m
18.006	frosted	6m



Black&White cover "easy-ON"

18.007	Black&White	2m
18.008	opaque grey	2m
18.009	Black&White	6m




Polycarbonate cover "easy-ON"






18.010	lens	2m
18.011	lens	6m



Patente Europea
Nº.: 13156605.1

Aluminium alloy extrusion process in accordance with: ISO 9001:2008 - ISO 14001 / Tolerances defined by: UNE-EN 755-9 / UNE-EN 12020-2
Theoretical weight: 0.273kg / Alloy: 6063 / Perimeter: 121mm / Anodising minimum: 15 microns
Aluminium purity: 95-98% / Material treatment: T-5 / Covers: Fireproof V0





Clip
20.007 chrome steel
20.008 black oxide finish



Ceiling hanger
70.001 silver
70.003 chrome



Hanger
70.002



Hanging KIT
21.001 silver set of 2 units
21.002 white set of 2 units
21.003 black set of 2 units
(clip not included)



Braided cable
42.070 steel





Supporting arm
22.006 silver anodised
22.007 black anodised
22.088 white anodised
Measurements: 170x50mm
* (clip not included)






Centre support
22.008 swivel support



Clip
20.019 metal





Centre support
22.009 aluminium



Side support
22.010 aluminium



Side support
22.011 aluminium




Side support
22.012 aluminium

MIAMI

Our BASIC led profile series for angles and ceiling suspension is manufactured in high purity aluminium and available in anodised silver, lacquered white and raw aluminium (on demand, we can supply different anodised and lacquered finishings. This profile has a wide range of applications, examples of which include ceiling suspended luminaires, luminaires for displaying paintings, wardrobe garment rails, floor or wall mounted luminaires, and others.

It can be used with led strips with a maximum width of 12.5mm and a power not greater than 30W/m. In order to obtain a more homogeneous illumination, while also making the dots invisible, we recommend the combined use of both our frosted covers and Canovelles-Barcelona-Gomera-COB ecoled strips.

We offer a 2 year guarantee on our profiles and covers.



Aluminium profile

13.007	anodised silver	2m
13.008	white lacquered	2m
13.009	raw	2m
13.010	anodised silver	6m
13.011	white lacquered	6m
13.012	raw	6m



Methacrylate cover

18.014	transparent	2m
18.015	frosted	2m
18.116	frosted	2m
18.018	opal	3m
18.016	transparent	6m
18.017	frosted	6m
18.115	frosted	6m



Plastic endcaps

19.091	white with hole
19.092	white without hole
19.093	grey with hole
19.094	grey without hole



Supporting arm

22.006	silver anodised
22.007	black anodised

Measurements: 170x50mm

* (clip not included)



Clip

20.005	transparent plastic
--------	---------------------



clip

20.019	metal
--------	-------

Paris complements can also be used



**MIAMI profile
+ hanging KIT "21.001"**



Aluminium alloy extrusion process in accordance with: ISO 9001:2008 - ISO 14001 / Tolerances defined by: UNE-EN 755-9 / UNE-EN 12020-2
Theoretical weight: 0.265kg / Alloy: 6063 / Perimeter: 125mm / Anodising minimum: 15 microns
Aluminium purity: 95-98% / Material treatment: T-5 / Covers: methacrylate (greater protection against UV rays)

Made with Paris XL led Profile
Cortesy of singular.design



Our PROFESSIONAL led profile series for surfaces and ceiling suspension is manufactured in high purity aluminium and available in anodised silver, black and inox. It covers many uses where we require a width greater than the standard, examples of which include ceiling suspended luminaires, luminaires for displaying paintings, and others. Additionally, its optimum width allows us to use wider led strips for an increased heat dissipation and a wider angle of light emission.

Its upper channel allows us to manufacture square, rectangular or L-shaped hanging luminaires.

By combining its "easy-ON" cover (available in 6 different finishings), we provide an IP65 to the luminaire. Therefore, the profile can be used in places with high levels of humidity, for example bathrooms, kitchens, gyms, spas, cold storage chambers, fridges, or others.


The profile and its covers are available in lengths of 2 and 6 metres, thus enabling us to carry about large projects where all the profiles don't need joints. Suitable for led strips with a maximum width of 20mm. Apart from using our flexible led strips, Canovelles-Barcelona-Gomera-COB we can also use rigid ones.

We offer a 10 year guarantee on profiles and a 4 year guarantee on covers.

PARIS XL




IP65



Scale 1:1

simple cover



Flex&Cover Arles
See page 170



Perfil de aluminio

13.013	anodised silver	2m
13.015	anodised black	2m
13.016	anodised silver	6m
13.018	anodised black	6m



Aluminium endcaps

19.095	anodised silver
19.096	anodised black



Clip


20.020	transparent polycarbonate
20.021	metal



Supporting arm

22.006	silver anodised
22.007	black anodised

Measurements: 170x50mm
* (clip not included)



Polycarbonate cover "easy-ON"

18.022	transparent	2m
18.023	opal	2m
18.024	frosted	2m
18.025	transparent	6m
18.026	opal	6m
18.027	frosted	6m



Black&White cover "easy-ON"

18.028	Black&White	2m
18.029	Black&White	6m



Polycarbonate cover "easy-ON"

18.030	lens	2m
18.031	lens	6m



Patente Europea
Nº.: 13156605.1

Aluminium alloy extrusion process in accordance with: ISO 9001:2008 - ISO 14001 / Tolerances defined by: UNE-EN 755-9 / UNE-EN 12020-2
Theoretical weight: 0.740kg / Alloy: 6063 / Perimeter: 341mm / Anodising minimum: 15 microns
Aluminium purity: 95-98% / Material treatment: T-5 / Covers: Fireproof V0



Inner plate

22.013 aluminium 2 m



90° angle bracket

22.003 steel



Hanging KIT

21.001 silver set of 2 units
21.002 white set of 2 units
21.003 black set of 2 units
(clip not included)



Profile joint




22.005 steel



120° angle bracket

22.004 steel

Scale 1:1



By applying the lens cover on the Paris XL profile together with the flexible led strip we achieve 3 different light angles.
The information is just approximate. Please check with our technical department



Hanging KIT
"21.001"


led profile by Luz Negra

Our PROFESSIONAL led profile series which is manufactured in Black&White, is ideal for surfaces, ceiling suspended luminaires, floor or wall mounted luminaires and similar.


It is suitable for led strips with a maximum width of 15mm and a power not greater than 20W/m. In order to obtain a more homogeneous illumination, while also making a non dot effect, we recommend combining it with our Elite series of led strips, COB and also our ecoled digital model Hawaii RGB.

We offer a 2 year guarantee.

OSLO Black&White



Scale 1:1



Polycarbonate profile

13.020 black frosted 3m



Endcaps

19.104 methacrylate



Surface endcaps

19.100 blue plastic
19.101 white plastic
19.102 black plastic
19.103 red plastic



Inner plate

22.014 aluminium
(2000x23x1mm)




Hanging KIT

21.001 silver set of 2 units
21.002 white set of 2 units
21.003 black set of 2 units
(clip not included)



Clip

20.020 transparent polycarbonate
20.021 metal



Oslo Black&White with digital led strip



Plastic profile extrusion process in accordance with: ISO 9001
Theoretical weight: 0.275kg/m / Raw material: acrylic PMMA / Perimeter: 119.4mm / Acrylic purity: 99.95%


Our PROFESSIONAL led profile series for surfaces and ceiling suspension is manufactured in white frosted polycarbonate. The profile is ideal for surface applications, for example ceiling suspended luminaires, floor or wall mounted luminaires, and similar.

It is suitable for led strips with a maximum width of 15mm and a power not greater than 20W/m. In order to obtain a more homogeneous illumination, while also making the dots invisible, we recommend combining it with our Canovelles-Barcelona-Gomera-COB ecoled strips.

We offer a 2 year guarantee.

OSLO

Scale 1:1



Polycarbonate profile

13.019 white frosted 3m



Endcaps

19.099 frosted methacrylate



Surface endcaps

19.100 blue plastic
19.101 white plastic
19.102 black plastic
19.103 red plastic



Inner plate

22.014 aluminium
(2000x23x1mm)





Hanging KIT

21.001 silver set of 2 units
21.002 white set of 2 units
21.003 black set of 2 units
(clip not included)



Clip

20.020 transparent polycarbonate
20.021 metal



Plastic profile extrusion process in accordance with: ISO 9001
Theoretical weight: 0.275kg/m / Raw material: acrylic PMMA / Perimeter: 119.4mm / Acrylic purity: 99.95%