

LED DIGITAL

COZUMEL

TIRAS FLEXIBLES

Ref: 35.004

RGB DIGITAL


Tira flexible con led digital RGB serie "PRO"
IP20 con 30 leds/metro y cortable cada led.
Requiere uso de led profile para disipación.

PCB de 10 mm.

Conexión máxima en circuito abierto: 5m.


Vida útil: 50.000h*

*En función de la disipación del perfil, de las horas diarias trabajadas y de la temperatura externa ambiental de trabajo.



Potencia (W)	5W/m
Voltaje (V)	12V
Tipo de IC	WS2812
Lumens	112 Lm/m
CRI	>40
Control del led	led a led
Emisión de luz	120°
Estanqueidad (IP)	IP20
Nº leds/m	30
Medidas	5000x10x2.5mm
Cortable	cada 33.2mm
PCB	10mm
Temperatura trabajo	-20°C / +60°C
Apto para	interior
Embalaje	1 rollo/5m
Garantía	3 años

Aprobado por: 




BARCELONA
C/ Carles Buhigues, 13
08420 Canovelles
Info@luznegra.net
Tel: +34 938 402 598

MADRID
C/ Adaptación, 27
28906 Getafe
centro@luznegra.net
Tel: +34 916 416 081

PARIS
113 Avenue Joffre
77450 Esbly
france@luznegra.net
Tel: +33 (0) 160 426 585

Spectrum Test Report



Color Parameters:

Chromaticity Coordinate: $x=0.2161$ $y=0.2465$ $u'=0.1564$ $v'=0.4015$
 CCT=100000K (Duv=0.0243) Dominant WL:Ld =481.4nm Purity=47.3%
 Ratio:R=18.7% G=62.6% B=18.6%; Peak WL:Lp=468.7nm FWHM=20.4nm
 Render Index:Ra=44.2 CRI=41.7 TM30:Rf=32 Rg=98
 R1 =46 R2 =45 R3 =38 R4 =58 R5 =65 R6 =42 R7 =43
 R8 =15 R9 =0 R10=0 R11=74 R12=56 R13=38 R14=63 R15=26

Photo Parameters:

Flux = 111.6 lm Eff. : 25.26 lm/W Fe = 543.5 mW Scotopic:552.51 S/P:4.9527





Electrical parameters:

V = 11.998 V I = 0.3681 A P = 4.416 W PF = 1.000

Status: Integral T = 2000 ms Ip = 38740 (59%)


Model:Ecoled Cozumel	Number: 35.004
Tester:Sergio Carneros	Date:26-5-2021
Temperature:25Deg	Humidity:57%
Manufacturer:Luz Negra S.L	Remarks:100cm de tira flexible

Rf: 32 CCT: 100000 K u': 0.1564
Rg: 98 Duv: 0.0243 v': 0.4015



Model:Ecoled Cozumel
Tester:Sergio Carneros
Temperature:25Deg
Manufacturer:Luz Negra S.L

Number: 35.004
Date:26-5-2021
Humidity:57%
Remarks:100cm de tira flexible



Hue Bin	Hue Angle	Rf	Graphic shift(%)	
			Chroma	Hue
1	0.0° - 22.5°	19	40	6
2	22.5° - 45.0°	5	32	-24
3	45.0° - 67.5°	9	23	-58
4	67.5° - 90.0°	3	-6	-58
5	90.0° - 112.5°	12	-32	-34
6	112.5° - 135.0°	57	-23	1
7	135.0° - 157.5°	62	-1	16
8	157.5° - 180.0°	51	16	18
9	180.0° - 202.5°	57	33	9
10	202.5° - 225.0°	48	14	-18
11	225.0° - 247.5°	40	16	-32
12	247.5° - 270.0°	13	-4	-39
13	270.0° - 292.5°	44	-19	-30
14	292.5° - 315.0°	36	-22	13
15	315.0° - 337.5°	43	1	31
16	337.5° - 360.0°	37	15	22

Model:Ecoled Cozumel
Tester:Sergio Carneros
Temperature:25Deg
Manufacturer:Luz Negra S.L

Number: 35.004
Date:26-5-2021
Humidity:57%
Remarks:100cm de tira flexible