

Ref: 40.030

**Features:**

- Protections: short circuit / over current / over voltage
- Cooling by free air convection
- Universal AC input range
- Protection degree: IP67
- Protection class II
- Constant voltage design



Electrical characteristics	Power (W)	100W
	Voltage (V)	12V
	Output current range (A)	0~8.3A
Input specifications	Input voltage range	90-264Vac
	Input frequency range	47Hz - 63Hz
	Efficiency	85%
	Input AC current	1.8A/115VAC, 0.9A / 230VAC
	Inrush current (typ.)	35A / 230VAC; T <sub>WIDTH</sub> = 1200μs
	Leakage current max.	0.25mA / 240VAC
Output specifications	Output rated current	8.3A
	Output line regulation	±1%
	Output load regulation	±2%
	Output tolerance	±3%
	Ripple and noise	200mV
	Setup, rise time	700ms, 50ms / 230VAC at full load
	Hold up time	40ms / 230VAC at full load
Protections	Over Current	Range: 110% - 150% rated current / Type: hiccup mode, auto-recovery.
	Short circuit	Type: hiccup mode, auto-recovery.
	Over voltage	24V / Type: hiccup mode, auto-recovery.
Working environment	Working temperature	-30°C - 70°C (Refer to Derating Curve)
	Working humidity	20 - 95% RH non-condensing
	Storage temperature and humidity	-40°C - 80°C, 10 - 95% RH non-condensing
	Temperature coefficient	± 0.03% / °C (0°C - 50°C)
	Vibration	10 - 500Hz, 2G, 10min / cycle, period for 60min. each along X, Y, Z axes
Other	Dimension	190x52x37mm
	Weight	0.60Kg
	Guarantee	5 years



**Assembly and safety information**

**Applied standards:**

- EN 61347-1
- EN 61347-2-13
- EN 55024
- EN 61000-3-2
- EN 61000-3-3
- EN 61547
- EN 61000-4-2
- EN 61000-4-3
- EN 61000-4-4
- EN 61000-4-5
- EN 61000-4-6
- EN 61000-4-8
- EN 61000-4-11
- EN 55015

Measurements:






Diagram:




Graphics:

Derating curve



Static characteristic



Lifetime UV. Ambient temperature curve

