


LUMINAIRE PHOTOMETRIC TEST REPORT


NAME: Lanzarote 3200k	TYPE:	WEIGHT:1
SPEC.:	DIM.: 3x10x500mm	SERIAL No.:
MFR.: Luz Negra s.l.	SUR.:22	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 90.11 lm/W			
MODEL	33.015	I _{max} (cd)	315.2	S/MH(C0/180)	1.26
NOMINAL POWER(W)	18w/m	LOR(%)	100.0	S/MH(C90/270)	1.27
RATED VOLTAGE(V)	24,4	TOTAL FLUX(lm)	936.44	η UP,DN(C0-180)	0.1,50.8
NOMINAL FLUX(lm)	936.444	CIE CLASS	DIRECT	η UP,DN(C180-360)	0.1,48.9
LAMPS INSIDE	1	η up(%)	0.3	CIBSE SHR NOM	1.25
TEST VOLTAGE(V)	24,4	η down(%)	99.7	CIBSE SHR MAX	1.35

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25DEG
Operators:Marçal Huguet
Test Date:March 2021

γ Range: 0 - 110DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.400
Humidity:37%
Test Distance:8.200m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum,lamp
10	312.0	312.2	310.8	309.0	308.2	308.1	309.6	311.4	0- 10	29.83	29.83	3.19,3.19
20	299.5	299.3	296.7	293.2	291.8	291.6	294.1	297.8	10- 20	85.85	115.7	12.4,12.4
30	277.0	276.9	272.9	268.3	266.4	266.0	269.0	274.5	20- 30	131.2	246.9	26.4,26.4
40	245.2	245.0	240.0	234.6	232.3	231.4	234.4	241.6	30- 40	160.1	407.0	43.5,43.5
50	204.3	204.3	198.6	192.8	190.1	188.5	191.2	199.5	40- 50	168.2	575.2	61.4,61.4
60	154.9	155.5	149.9	144.1	140.9	138.6	140.8	149.4	50- 60	153.9	729.1	77.9,77.9
70	98.97	100.3	95.81	90.35	86.37	83.82	86.02	93.15	60- 70	118.4	847.5	90.5,90.5
80	41.04	43.15	41.95	36.89	32.13	31.72	34.17	37.54	70- 80	67.54	915.1	97.7,97.7
90	2.287	4.098	0.8730	4.971	1.254	4.092	0.6407	3.646	80- 90	18.92	934.0	99.7,99.7
100	0.7605	0.6748	0.7368	0.6935	0.9601	0.8460	0.7910	0.7896	90-100	1.407	935.4	99.9,99.9
110	0.9345	0.9552	0.9915	0.9989	1.165	1.179	1.158	1.112	100-110	0.9751	936.4	100,100
120	0	0	0	0	0	0	0	0	110-120	0.0562	936.4	100,100
130	0	0	0	0	0	0	0	0	120-130	0	936.4	100,100
140	0	0	0	0	0	0	0	0	130-140	0	936.4	100,100
150	0	0	0	0	0	0	0	0	140-150	0	936.4	100,100
160	0	0	0	0	0	0	0	0	150-160	0	936.4	100,100
170	0	0	0	0	0	0	0	0	160-170	0	936.4	100,100
180	0	0	0	0	0	0	0	0	170-180	0	936.4	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25DEG
 Operators:Marçal Huguet
 Test Date:March 2021

γ Range: 0 - 110DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.400
 Humidity:37%
 Test Distance:8.200m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

NAME: Lanzarote 3200k	TYPE:	WEIGHT:1
SPEC.:	DIM.: 3x10x500mm	SERIAL No.:
MFR.: Luz Negra s.l.	SUR.:22	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25DEG
Operators: Marçal Huguet
Test Date: March 2021

γ Range: 0 - 110DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.400
Humidity: 37%
Test Distance: 8.200m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

NAME: Lanzarote 3200k	TYPE:	WEIGHT:1
SPEC.:	DIM.: 3x10x500mm	SERIAL No.:
MFR.: Luz Negra s.l.	SUR.:22	Shielding Angle:

ρ_{cc}	80%			70%			50%			30%			10%			0
ρ_w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρ_{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio			Coefficients of Utilization(CU)												
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	.00
1.0	1.04	.99	.95	1.01	.97	.94	.97	.94	.91	.93	.90	.88	.89	.87	.85	.83
2.0	.90	.83	.77	.88	.82	.76	.85	.79	.74	.81	.77	.73	.78	.74	.71	.69
3.0	.79	.71	.64	.77	.70	.63	.74	.68	.62	.71	.66	.61	.69	.64	.60	.58
4.0	.70	.61	.54	.68	.60	.54	.66	.59	.53	.63	.57	.52	.61	.56	.51	.49
5.0	.62	.53	.46	.61	.52	.46	.59	.51	.46	.57	.50	.45	.55	.49	.44	.42
6.0	.56	.47	.40	.55	.46	.40	.53	.45	.40	.51	.45	.39	.50	.44	.39	.37
7.0	.51	.42	.36	.50	.41	.35	.48	.41	.35	.47	.40	.35	.45	.39	.35	.33
8.0	.46	.38	.32	.45	.37	.32	.44	.37	.31	.43	.36	.31	.42	.35	.31	.29
9.0	.42	.34	.28	.42	.34	.28	.41	.33	.28	.39	.33	.28	.38	.32	.28	.26
10.0	.39	.31	.26	.38	.31	.26	.37	.30	.26	.36	.30	.25	.36	.30	.25	.23



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25DEG
Operators: Marçal Huguet
Test Date: March 2021

γ Range: 0 - 110DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.400
 Humidity:37%
 Test Distance:8.200m [K=1.0000]
 Remarks:

WEC AND CCEC

NAME: Lanzarote 3200k	TYPE:	WEIGHT:1
SPEC.:	DIM.: 3x10x500mm	SERIAL No.:
MFR.: Luz Negra s.l.	SUR.:22	Shielding Angle:

ρ_{CC}	80%			70%			50%			30%			10%			0
ρ_W	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρ_{fC}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Wall Exitance Coefficients(WEC)															
0.0																
1.0	.314	.179	.057	.307	.175	.056	.293	.168	.054	.281	.162	.052	.270	.156	.050	
2.0	.295	.162	.050	.289	.159	.049	.277	.154	.048	.266	.149	.047	.256	.145	.046	
3.0	.273	.145	.043	.267	.143	.043	.257	.139	.042	.247	.135	.041	.238	.132	.041	
4.0	.251	.131	.038	.246	.129	.038	.237	.126	.038	.228	.123	.037	.220	.120	.036	
5.0	.232	.118	.034	.228	.117	.034	.220	.114	.034	.212	.112	.033	.205	.109	.033	
6.0	.215	.108	.031	.211	.107	.031	.204	.105	.030	.197	.102	.030	.191	.100	.030	
7.0	.200	.099	.028	.197	.098	.028	.190	.096	.028	.184	.094	.027	.178	.093	.027	
8.0	.187	.091	.026	.184	.090	.026	.178	.089	.025	.172	.087	.025	.167	.086	.025	
9.0	.175	.085	.024	.172	.084	.024	.167	.083	.023	.162	.081	.023	.157	.080	.023	
10.0	.164	.079	.022	.162	.078	.022	.157	.077	.022	.153	.076	.022	.148	.075	.021	

ρ_{CC}	80%			70%			50%			30%			10%			0
ρ_W	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρ_{fC}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Ceiling Cavity Exitance Coefficients(CCEC)															
0.0	.192	.192	.192	.164	.164	.164	.112	.112	.112	.064	.064	.064	.021	.021	.021	
1.0	.183	.158	.136	.156	.136	.117	.107	.093	.081	.062	.054	.047	.020	.017	.015	
2.0	.175	.134	.100	.150	.115	.086	.103	.080	.060	.059	.046	.035	.019	.015	.011	
3.0	.167	.116	.076	.143	.100	.066	.098	.070	.046	.057	.041	.027	.018	.013	.009	
4.0	.159	.103	.060	.137	.089	.052	.094	.062	.037	.054	.036	.022	.018	.012	.007	
5.0	.152	.093	.049	.131	.080	.043	.090	.056	.030	.052	.033	.018	.017	.011	.006	
6.0	.145	.084	.041	.124	.073	.036	.086	.051	.025	.050	.030	.015	.016	.010	.005	
7.0	.138	.077	.035	.119	.067	.031	.082	.047	.022	.048	.028	.013	.015	.009	.004	
8.0	.131	.072	.031	.113	.062	.027	.078	.044	.019	.046	.026	.011	.015	.008	.004	
9.0	.125	.067	.027	.108	.058	.024	.075	.041	.017	.044	.024	.010	.014	.008	.003	
10.0	.120	.062	.024	.103	.054	.021	.072	.038	.015	.042	.023	.009	.014	.007	.003	

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25DEG
 Operators:Marçal Huguet
 Test Date:March 2021

γ Range: 0 - 110DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.400
 Humidity:37%
 Test Distance:8.200m [K=1.0000]
 Remarks:

UGR(Unified Glare Rating) Table

NAME: Lanzarote 3200k					TYPE:		WEIGHT:1				
SPEC.:					DIM.: 3x10x500mm		SERIAL No.:				
MFR.: Luz Negra s.l.					SUR.:22		Shielding Angle:				
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H y = 2H	2H	14.9	16.4	15.2	16.7	16.9	14.8	16.3	15.1	16.5	16.7
	3H	16.5	18.0	16.8	18.2	18.4	16.4	17.8	16.7	18.0	18.3
	4H	17.2	18.5	17.5	18.8	19.1	17.0	18.4	17.3	18.6	18.9
	6H	17.6	18.9	18.0	19.2	19.5	17.5	18.8	17.8	19.0	19.3
	8H	17.8	19.0	18.1	19.3	19.6	17.7	18.9	18.0	19.2	19.5
	12H	17.8	19.0	18.2	19.3	19.6	17.8	18.9	18.1	19.2	19.6
4H	2H	15.6	16.9	15.9	17.2	17.4	15.5	16.8	15.8	17.1	17.3
	3H	17.4	18.6	17.7	18.9	19.2	17.3	18.4	17.6	18.7	19.0
	4H	18.1	19.2	18.5	19.6	19.9	18.0	19.1	18.4	19.4	19.8
	6H	18.7	19.7	19.1	20.0	20.4	18.6	19.6	19.0	19.9	20.3
	8H	18.9	19.8	19.3	20.2	20.6	18.8	19.7	19.3	20.1	20.5
	12H	19.0	19.8	19.5	20.2	20.6	19.0	19.8	19.4	20.2	20.6
8H	4H	18.4	19.3	18.9	19.7	20.1	18.3	19.2	18.7	19.6	20.0
	6H	19.2	19.9	19.6	20.3	20.8	19.1	19.8	19.5	20.2	20.7
	8H	19.4	20.1	19.9	20.5	21.0	19.4	20.1	19.9	20.5	20.9
	12H	19.6	20.2	20.1	20.6	21.1	19.7	20.2	20.1	20.7	21.2
12H	4H	18.5	19.3	18.9	19.7	20.1	18.3	19.2	18.8	19.6	20.0
	6H	19.2	19.9	19.7	20.3	20.8	19.2	19.8	19.6	20.2	20.7
	8H	19.5	20.1	20.0	20.6	21.0	19.5	20.1	20.0	20.5	21.0
Variations with the observer position at spacings:											
S = 1.0H		+ 0.1 / - 0.2					+ 0.1 / - 0.2				
1.5H		+ 0.2 / - 0.3					+ 0.2 / - 0.3				
2.0H		+ 0.2 / - 0.3					+ 0.2 / - 0.4				

CIE Pub.117, 936.4 lm Total Lamp Luminous Flux Correct ($8\log(F/F_0) = -0.2$)

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25DEG
Operators:Marçal Huguet
Test Date:March 2021

γ Range: 0 - 110DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.400
Humidity:37%
Test Distance:8.200m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

NAME: Lanzarote 3200k	TYPE:	WEIGHT:1
SPEC.:	DIM.: 3x10x500mm	SERIAL No.:
MFR.: Luz Negra s.l.	SUR.:22	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	57	45	38	56	45	38	55	44	38	31
0.80	67	55	48	66	55	47	64	54	47	40
1.00	75	64	57	74	63	56	72	65	56	49
1.25	82	72	65	81	71	64	78	70	63	56
1.50	88	77	70	86	77	70	83	75	69	61
2.00	94	86	79	93	85	78	89	82	77	69
2.50	98	91	84	96	89	83	92	86	82	73
3.00	102	95	89	100	93	88	96	90	86	77
4.00	106	100	95	104	98	94	99	95	91	82
5.00	108	103	99	106	102	98	101	98	95	85
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25DEG
Operators:Marçal Huguet
Test Date:March 2021

γ Range: 0 - 110DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.400
Humidity:37%
Test Distance:8.200m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

NAME: Lanzarote 3200k	TYPE:	WEIGHT:1
SPEC.:	DIM.: 3x10x500mm	SERIAL No.:
MFR.: Luz Negra s.l.	SUR.:22	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25DEG
Operators: Marçal Huguet
Test Date: March 2021

γ Range: 0 - 110DEG
γ Interval: 1.0DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.400
Humidity: 37%
Test Distance: 8.200m [K=1.0000]
Remarks:

AAI Figure

NAME: Lanzarote 3200k	TYPE:	WEIGHT:1
SPEC.:	DIM.: 3x10x500mm	SERIAL No.:
MFR.: Luz Negra s.l.	SUR.:22	Shielding Angle:




Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25DEG
Operators: Marçal Huguet
Test Date: March 2021

γ Range: 0 - 110DEG
γ Interval: 1.0DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.400
Humidity: 37%
Test Distance: 8.200m [K=1.0000]
Remarks:

ISOLUX DIAGRAM

NAME: Lanzarote 3200k	TYPE:	WEIGHT:1
SPEC.:	DIM.: 3x10x500mm	SERIAL No.:
MFR.: Luz Negra s.l.	SUR.:22	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25DEG
Operators: Marçal Huguet
Test Date: March 2021

γ Range: 0 - 110DEG
γ Interval: 1.0DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.400
Humidity: 37%
Test Distance: 8.200m [K=1.0000]
Remarks:

LED Avg.L Report

NAME: Lanzarote 3200k	TYPE:	WEIGHT:1
SPEC.:	DIM.: 3x10x500mm	SERIAL No.:
MFR.: Luz Negra s.l.	SUR.:22	Shielding Angle:


AvgL	cd/m2
L_0~180(65)av	1430
L_0~180(75)av	1237
L_0~180(85)av	791
L_90~270(65)av	1403
L_90~270(75)av	1224
L_90~270(85)av	1018
L_45(65)av	1419
L_45(75)av	1234
L_45(85)av	882

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25DEG
Operators:Marçal Huguet
Test Date:March 2021

γ Range: 0 - 110DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.400
Humidity:37%
Test Distance:8.200m [K=1.0000]
Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 25DEG
 Operators: Marçal Huguet
 Test Date: March 2021

γ Range: 0 - 110DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.400
 Humidity: 37%
 Test Distance: 8.200m [K=1.0000]
 Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

NAME: Lanzarote 3200k	TYPE:	WEIGHT:1
SPEC.:	DIM.: 3x10x500mm	SERIAL No.:
MFR.: Luz Negra s.l.	SUR.:22	Shielding Angle:

Table--1

UNIT: cd

C (DEG) γ (DEG)	0	22.5	45	67.5	90	112.5	135	157.5	180	202.5	225	247.5	270	292.5	315	337.5			
0	315	315	315	315	315	315	315	315	315	315	315	315	315	315	315	315			
5	315	315	315	314	314	314	313	313	313	313	313	313	313	314	314	314			
10	312	312	312	312	311	310	309	309	308	308	308	309	310	310	311	312			
15	307	307	307	306	305	304	302	302	301	301	301	302	303	304	306	306			
20	300	300	299	298	297	295	293	293	292	291	292	293	294	296	298	299			
25	289	290	289	288	286	284	282	281	280	280	280	281	283	285	287	289			
30	277	278	277	276	273	271	268	268	266	265	266	267	269	271	274	276			
35	262	263	262	261	258	256	253	252	250	249	250	250	253	255	259	261			
40	245	246	245	243	240	238	235	234	232	231	231	232	234	237	242	244			
45	226	227	226	224	220	218	215	214	212	211	211	211	214	217	222	224			
50	204	206	204	202	199	196	193	192	190	189	189	188	191	194	200	203			
55	181	182	181	179	175	173	169	168	166	164	164	164	167	170	175	179			
60	155	157	155	153	150	148	144	143	141	139	139	138	141	144	149	153			
65	128	130	129	127	123	121	118	116	114	112	112	111	114	116	122	126			
70	99.0	101	100	98.9	95.8	93.8	90.4	88.2	86.4	84.2	83.8	83.7	86.0	88.4	93.2	97.0			
75	69.6	71.9	71.5	70.5	67.9	66.1	62.9	60.4	58.5	56.5	56.6	56.7	58.9	60.7	64.5	67.7			
80	41.0	43.2	43.2	43.7	42.0	40.4	36.9	34.2	32.1	30.7	31.7	32.5	34.2	35.3	37.5	39.6			
85	16.5	17.4	17.4	20.8	20.1	19.6	16.2	12.8	11.0	10.9	13.0	14.6	15.4	15.6	14.9	15.8			
90	2.29	3.36	4.10	4.99	0.87	6.55	4.97	2.59	1.25	2.24	4.09	4.93	0.64	3.48	3.65	3.04			
95	0.71	0.94	1.01	0.61	0.48	0.60	1.22	1.19	1.02	1.35	1.45	0.77	0.62	0.68	1.10	1.06			
100	0.76	0.75	0.67	0.63	0.74	0.65	0.69	0.79	0.96	0.95	0.85	0.99	0.79	0.77	0.79	0.89			
105	0.77	0.79	0.80	0.92	0.81	0.82	0.83	0.85	0.98	1.00	1.00	1.27	0.97	0.94	0.94	0.92			
110	0.93	0.94	0.96	1.21	0.99	0.99	1.00	1.02	1.16	1.18	1.18	1.46	1.16	1.12	1.11	1.08			
115	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00			
120	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00			
125	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00			
130	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00			
135	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00			
140	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00			
145	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00			
150	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00			
155	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00			
160	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00			
165	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00			
170	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00			
175	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00			
180	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00			

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25DEG
Operators: Marçal Huguet
Test Date: March 2021

γ Range: 0 - 110DEG
γ Interval: 1.0DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.400
Humidity: 37%
Test Distance: 8.200m [K=1.0000]
Remarks: