


LUMINAIRE PHOTOMETRIC TEST REPORT

NAME: Lanzarote 4200k	TYPE:	WEIGHT:1
SPEC.:	DIM.: 3x10x500mm	SERIAL No.:
MFR.: Luz Negra s.l.	SUR.:22	Shielding Angle:


DATA OF LAMP		PHOTOMETRIC DATA				Eff: 94.30 lm/W
MODEL	33.014	I _{max} (cd)	331.2	S/MH(C0/180)	1.30	
NOMINAL POWER(W)	18w/m	LOR(%)	100.0	S/MH(C90/270)	1.27	
RATED VOLTAGE(V)	24,4	TOTAL FLUX(lm)	982.23	η UP,DN(C0-180)	0.1,50.4	
NOMINAL FLUX(lm)	982.226	CIE CLASS	DIRECT	η UP,DN(C180-360)	0.1,49.3	
LAMPS INSIDE	1	η up(%)	0.3	CIBSE SHR NOM	1.25	
TEST VOLTAGE(V)	24,4	η down(%)	99.7	CIBSE SHR MAX	1.35	

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



AVERAGE BEAM ANGLE(50%):115.6 DEG

C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25DEG
Operators:Marçal Huguet
Test Date:March 2021

γ Range: 0 - 110DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.400
Humidity:37%
Test Distance:8.200m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum, lamp
10	323.9	325.1	326.5	327.6	327.9	326.6	325.3	324.2	0- 10	31.35	31.35	3.19,3.19
20	306.9	309.1	311.7	313.7	314.3	311.9	309.1	307.2	10- 20	90.20	121.6	12.4,12.4
30	280.0	283.2	286.8	289.7	290.5	286.9	282.7	280.2	20- 30	137.8	259.4	26.4,26.4
40	244.1	247.9	252.1	255.7	256.7	252.0	246.6	244.2	30- 40	168.1	427.5	43.5,43.5
50	199.8	204.2	208.5	212.2	212.9	207.3	201.2	199.4	40- 50	176.5	603.9	61.5,61.5
60	148.3	153.0	157.3	160.3	160.2	154.2	148.2	147.2	50- 60	161.2	765.2	77.9,77.9
70	91.48	96.62	100.6	102.0	100.5	94.91	90.26	89.90	60- 70	123.7	888.9	90.5,90.5
80	35.34	41.54	45.30	42.94	40.02	36.78	36.51	35.62	70- 80	70.56	959.4	97.7,97.7
90	1.469	6.051	0.7547	4.831	1.964	3.810	0.7205	4.765	80- 90	20.20	979.6	99.7,99.7
100	0.8601	0.7084	0.7306	0.6584	0.8941	0.8399	0.8456	0.8724	90-100	1.519	981.1	99.9,99.9
110	1.059	1.050	1.463	0.9943	1.146	1.181	1.244	1.221	100-110	1.027	982.2	100,100
120	0	0	0	0	0	0	0	0	110-120	0.0603	982.2	100,100
130	0	0	0	0	0	0	0	0	120-130	0	982.2	100,100
140	0	0	0	0	0	0	0	0	130-140	0	982.2	100,100
150	0	0	0	0	0	0	0	0	140-150	0	982.2	100,100
160	0	0	0	0	0	0	0	0	150-160	0	982.2	100,100
170	0	0	0	0	0	0	0	0	160-170	0	982.2	100,100
180	0	0	0	0	0	0	0	0	170-180	0	982.2	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25DEG
 Operators:Marçal Huguet
 Test Date:March 2021

γ Range: 0 - 110DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.400
 Humidity:37%
 Test Distance:8.200m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

NAME: Lanzarote 4200k	TYPE:	WEIGHT:1
SPEC.:	DIM.: 3x10x500mm	SERIAL No.:
MFR.: Luz Negra s.l.	SUR.:22	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25DEG
Operators: Marçal Huguet
Test Date: March 2021

γ Range: 0 - 110DEG
γ Interval: 1.0DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.400
Humidity: 37%
Test Distance: 8.200m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

NAME: Lanzarote 4200k	TYPE:	WEIGHT:1
SPEC.:	DIM.: 3x10x500mm	SERIAL No.:
MFR.: Luz Negra s.l.	SUR.:22	Shielding Angle:

ρcc	80%			70%			50%			30%			10%			0
ρw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρfc	20%			20%			20%			20%			20%			0
RCR	Coefficients of Utilization(CU)															
	RCR:Room Cavity Ratio															
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	.00
1.0	1.04	.99	.95	1.01	.97	.94	.97	.94	.91	.93	.90	.88	.89	.87	.85	.83
2.0	.90	.83	.77	.88	.82	.76	.85	.79	.74	.81	.77	.73	.78	.74	.71	.69
3.0	.79	.71	.64	.77	.70	.63	.74	.68	.62	.71	.66	.61	.69	.64	.60	.58
4.0	.70	.61	.54	.68	.60	.54	.66	.59	.53	.63	.57	.52	.61	.56	.51	.49
5.0	.62	.53	.46	.61	.52	.46	.59	.51	.46	.57	.50	.45	.55	.49	.44	.42
6.0	.56	.47	.40	.55	.46	.40	.53	.45	.40	.51	.45	.39	.50	.44	.39	.37
7.0	.51	.42	.36	.50	.41	.35	.48	.41	.35	.47	.40	.35	.45	.39	.35	.33
8.0	.46	.38	.32	.45	.37	.32	.44	.37	.31	.43	.36	.31	.42	.35	.31	.29
9.0	.42	.34	.28	.42	.34	.28	.41	.33	.28	.39	.33	.28	.38	.32	.28	.26
10.0	.39	.31	.26	.39	.31	.26	.37	.30	.26	.37	.30	.25	.36	.30	.25	.23



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25DEG
Operators: Marçal Huguet
Test Date: March 2021

γ Range: 0 - 110DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.400
 Humidity:37%
 Test Distance:8.200m [K=1.0000]
 Remarks:

WEC AND CCEC

NAME: Lanzarote 4200k	TYPE:	WEIGHT:1
SPEC.:	DIM.: 3x10x500mm	SERIAL No.:
MFR.: Luz Negra s.l.	SUR.:22	Shielding Angle:

ρ_{CC}	80%			70%			50%			30%			10%			0
ρ_W	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρ_{fC}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Wall Exitance Coefficients(WEC)															
0.0																
1.0	.314	.179	.057	.307	.175	.056	.293	.168	.054	.281	.162	.052	.270	.156	.050	
2.0	.295	.162	.050	.289	.159	.049	.277	.154	.048	.266	.149	.047	.256	.145	.046	
3.0	.273	.145	.043	.267	.143	.043	.256	.139	.042	.247	.135	.041	.238	.132	.041	
4.0	.251	.131	.038	.246	.129	.038	.237	.126	.038	.228	.123	.037	.220	.120	.036	
5.0	.232	.118	.034	.228	.117	.034	.219	.114	.034	.212	.112	.033	.205	.109	.033	
6.0	.215	.108	.031	.211	.107	.031	.204	.104	.030	.197	.102	.030	.190	.100	.030	
7.0	.200	.099	.028	.197	.098	.028	.190	.096	.028	.184	.094	.027	.178	.092	.027	
8.0	.187	.091	.026	.184	.090	.026	.178	.089	.025	.172	.087	.025	.167	.086	.025	
9.0	.175	.085	.024	.172	.084	.024	.167	.083	.023	.162	.081	.023	.157	.080	.023	
10.0	.164	.079	.022	.162	.078	.022	.157	.077	.022	.153	.076	.022	.148	.075	.021	

ρ_{CC}	80%			70%			50%			30%			10%			0
ρ_W	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρ_{fC}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Ceiling Cavity Exitance Coefficients(CCEC)															
0.0	.192	.192	.192	.165	.165	.165	.112	.112	.112	.065	.065	.065	.021	.021	.021	
1.0	.183	.158	.136	.156	.136	.117	.107	.093	.081	.062	.054	.047	.020	.017	.015	
2.0	.175	.134	.100	.150	.115	.086	.103	.080	.060	.059	.046	.035	.019	.015	.011	
3.0	.167	.116	.076	.143	.100	.066	.098	.070	.046	.057	.041	.027	.018	.013	.009	
4.0	.159	.103	.060	.137	.089	.052	.094	.062	.037	.054	.036	.022	.018	.012	.007	
5.0	.152	.093	.049	.131	.080	.043	.090	.056	.030	.052	.033	.018	.017	.011	.006	
6.0	.145	.084	.041	.124	.073	.036	.086	.051	.025	.050	.030	.015	.016	.010	.005	
7.0	.138	.078	.035	.119	.067	.031	.082	.047	.022	.048	.028	.013	.015	.009	.004	
8.0	.132	.072	.031	.113	.062	.027	.078	.044	.019	.046	.026	.011	.015	.008	.004	
9.0	.125	.067	.027	.108	.058	.024	.075	.041	.017	.044	.024	.010	.014	.008	.003	
10.0	.120	.062	.024	.103	.054	.021	.072	.038	.015	.042	.023	.009	.014	.007	.003	

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25DEG
 Operators:Marçal Huguet
 Test Date:March 2021

γ Range: 0 - 110DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.400
 Humidity:37%
 Test Distance:8.200m [K=1.0000]
 Remarks:

UGR(Unified Glare Rating) Table

NAME: Lanzarote 4200k	TYPE:	WEIGHT:1
SPEC.:	DIM.: 3x10x500mm	SERIAL No.:
MFR.: Luz Negra s.l.	SUR.:22	Shielding Angle:

ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
x = 2H y = 2H	14.4	16.0	14.7	16.2	16.4	14.6	16.2	14.9	16.4	16.6
3H	15.9	17.4	16.2	17.6	17.8	16.2	17.7	16.5	17.9	18.1
4H	16.5	17.9	16.8	18.1	18.4	16.9	18.2	17.2	18.5	18.8
6H	16.9	18.2	17.2	18.4	18.7	17.4	18.7	17.7	18.9	19.2
8H	17.0	18.2	17.3	18.5	18.8	17.6	18.8	17.9	19.1	19.4
12H	17.0	18.2	17.4	18.5	18.8	17.7	18.9	18.1	19.2	19.5
4H 2H	15.1	16.4	15.4	16.7	16.9	15.2	16.6	15.5	16.8	17.1
3H	16.8	18.0	17.1	18.3	18.6	17.0	18.2	17.4	18.5	18.8
4H	17.5	18.5	17.9	18.9	19.2	17.8	18.9	18.2	19.2	19.6
6H	18.0	18.9	18.4	19.3	19.7	18.4	19.4	18.9	19.8	20.1
8H	18.1	19.0	18.5	19.4	19.8	18.7	19.6	19.1	20.0	20.3
12H	18.2	19.0	18.6	19.4	19.8	18.9	19.7	19.3	20.1	20.5
8H 4H	17.8	18.7	18.2	19.0	19.4	18.1	19.0	18.5	19.3	19.7
6H	18.4	19.2	18.9	19.6	20.0	18.9	19.6	19.3	20.0	20.5
8H	18.6	19.3	19.1	19.7	20.2	19.2	19.9	19.7	20.3	20.8
12H	18.8	19.4	19.3	19.8	20.3	19.5	20.1	20.0	20.5	21.0
12H 4H	17.8	18.6	18.2	19.0	19.4	18.1	18.9	18.5	19.3	19.7
6H	18.5	19.1	19.0	19.6	20.0	18.9	19.6	19.4	20.0	20.5
8H	18.8	19.3	19.2	19.8	20.3	19.3	19.9	19.8	20.3	20.8

Variations with the observer position at spacings:

S = 1.0H	+ 0.2 / - 0.2	+ 0.1 / - 0.2
1.5H	+ 0.2 / - 0.3	+ 0.2 / - 0.3
2.0H	+ 0.2 / - 0.3	+ 0.1 / - 0.3

CIE Pub.117, 982.2 lm Total Lamp Luminous Flux Correct ($8\log(F/F_0) = -0.1$)

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25DEG
Operators:Marçal Huguet
Test Date:March 2021

γ Range: 0 - 110DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.400
Humidity:37%
Test Distance:8.200m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

NAME: Lanzarote 4200k	TYPE:	WEIGHT:1
SPEC.:	DIM.: 3x10x500mm	SERIAL No.:
MFR.: Luz Negra s.l.	SUR.:22	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	57	45	38	56	45	38	55	44	38	31
0.80	67	55	48	66	55	48	64	54	47	40
1.00	75	64	57	74	64	56	72	65	56	49
1.25	83	72	65	81	71	64	78	70	63	56
1.50	88	77	70	86	77	70	83	75	69	61
2.00	94	86	79	93	85	78	89	82	77	69
2.50	98	91	84	96	89	83	93	86	82	73
3.00	102	95	89	100	93	88	96	90	86	77
4.00	106	100	95	104	98	94	99	95	91	82
5.00	108	103	99	106	102	98	101	98	95	85
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25DEG
Operators:Marçal Huguet
Test Date:March 2021

γ Range: 0 - 110DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.400
Humidity:37%
Test Distance:8.200m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

NAME: Lanzarote 4200k	TYPE:	WEIGHT:1
SPEC.:	DIM.: 3x10x500mm	SERIAL No.:
MFR.: Luz Negra s.l.	SUR.:22	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25DEG
Operators: Marçal Huguet
Test Date: March 2021

γ Range: 0 - 110DEG
γ Interval: 1.0DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.400
Humidity: 37%
Test Distance: 8.200m [K=1.0000]
Remarks:

AAI Figure

NAME: Lanzarote 4200k	TYPE:	WEIGHT:1
SPEC.:	DIM.: 3x10x500mm	SERIAL No.:
MFR.: Luz Negra s.l.	SUR.:22	Shielding Angle:




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25DEG
Operators:Marçal Huguet
Test Date:March 2021

γ Range: 0 - 110DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.400
Humidity:37%
Test Distance:8.200m [K=1.0000]
Remarks:

ISOLUX DIAGRAM

NAME: Lanzarote 4200k	TYPE:	WEIGHT:1
SPEC.:	DIM.: 3x10x500mm	SERIAL No.:
MFR.: Luz Negra s.l.	SUR.:22	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25DEG
Operators: Marçal Huguet
Test Date: March 2021

γ Range: 0 - 110DEG
γ Interval: 1.0DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.400
Humidity: 37%
Test Distance: 8.200m [K=1.0000]
Remarks:

LED Avg.L Report

NAME: Lanzarote 4200k	TYPE:	WEIGHT:1
SPEC.:	DIM.: 3x10x500mm	SERIAL No.:
MFR.: Luz Negra s.l.	SUR.:22	Shielding Angle:


AvgL	cd/m2
L_0~180(65)av	1487
L_0~180(75)av	1275
L_0~180(85)av	829
L_90~270(65)av	1472
L_90~270(75)av	1294
L_90~270(85)av	1115
L_45(65)av	1482
L_45(75)av	1286
L_45(85)av	940

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25DEG
Operators:Marçal Huguet
Test Date:March 2021

γ Range: 0 - 110DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.400
Humidity:37%
Test Distance:8.200m [K=1.0000]
Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 25DEG
 Operators: Marçal Huguet
 Test Date: March 2021

γ Range: 0 - 110DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.400
 Humidity: 37%
 Test Distance: 8.200m [K=1.0000]
 Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

NAME: Lanzarote 4200k	TYPE:	WEIGHT:1
SPEC.:	DIM.: 3x10x500mm	SERIAL No.:
MFR.: Luz Negra s.l.	SUR.:22	Shielding Angle:

Table--1

UNIT: cd

C (DEG) γ (DEG)	0	22.5	45	67.5	90	112.5	135	157.5	180	202.5	225	247.5	270	292.5	315	337.5			
0	331	331	331	331	331	331	331	331	331	331	331	331	331	331	331	331			
5	329	329	329	330	330	330	331	331	331	331	330	330	329	329	329	329			
10	324	325	325	326	326	327	328	328	328	327	327	326	325	324	324	324			
15	317	318	318	320	320	321	322	322	322	322	321	319	318	317	317	317			
20	307	308	309	311	312	313	314	314	314	313	312	310	309	308	307	307			
25	295	296	297	299	300	302	303	304	304	302	301	298	297	295	295	295			
30	280	282	283	285	287	289	290	290	291	289	287	284	283	281	280	280			
35	263	266	267	269	271	273	274	275	275	273	271	267	266	264	264	264			
40	244	247	248	251	252	255	256	256	257	254	252	248	247	244	244	244			
45	223	226	227	230	231	234	235	236	236	233	231	227	225	222	223	223			
50	200	203	204	207	209	211	212	213	213	210	207	203	201	199	199	200			
55	175	178	179	182	184	186	187	188	188	184	182	177	176	173	174	175			
60	148	152	153	156	157	160	160	161	160	157	154	150	148	146	147	148			
65	120	124	125	128	129	132	132	132	131	128	125	121	119	118	119	120			
70	91.5	94.9	96.6	99.5	101	102	102	101	100	97.4	94.9	91.2	90.3	88.8	89.9	90.9			
75	62.5	65.9	68.1	71.1	72.1	73.2	72.0	70.8	69.5	66.8	64.9	62.5	61.9	60.8	61.4	62.1			
80	35.3	38.8	41.5	44.8	45.3	45.6	42.9	41.7	40.0	37.8	36.8	36.4	36.5	35.8	35.6	35.4			
85	13.2	16.4	19.6	22.8	22.3	21.6	17.2	16.9	15.7	13.9	13.3	15.6	16.6	16.5	15.4	14.0			
90	1.47	3.47	6.05	7.54	0.75	5.30	4.83	3.32	1.96	2.72	3.81	3.69	0.72	4.99	4.76	2.92			
95	1.01	1.31	1.35	0.66	0.51	0.58	0.92	1.05	0.92	1.14	1.22	0.83	0.66	0.78	1.54	1.49			
100	0.86	0.80	0.71	0.67	0.73	0.66	0.66	0.75	0.89	0.89	0.84	0.88	0.85	0.86	0.87	0.96			
105	0.87	0.87	0.86	0.87	1.18	0.83	0.81	0.82	0.96	0.96	0.98	1.29	1.04	1.04	1.03	1.03			
110	1.06	1.06	1.05	1.25	1.46	1.01	0.99	0.99	1.15	1.15	1.18	1.53	1.24	1.23	1.22	1.21			
115	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00			
120	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00			
125	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00			
130	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00			
135	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00			
140	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00			
145	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00			
150	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00			
155	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00			
160	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00			
165	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00			
170	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00			
175	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00			
180	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00			

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25DEG
Operators: Marçal Huguet
Test Date: March 2021

γ Range: 0 - 110DEG
γ Interval: 1.0DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.400
Humidity: 37%
Test Distance: 8.200m [K=1.0000]
Remarks: